



NOTES:

1. DIMENSIONS ARE IN METRES UNLESS SPECIFIED OTHERWISE.
2. TRAFFIC ISLAND PLAN IS INDICATIVE ONLY. DIMENSIONS AS SPECIFIED ON PLANS.
3. REFER TO BCC STD S300 FOR KERB DIMENSIONS.
4. CONCRETE STRENGTH 32MPa AT 28 DAYS FOR ALL CONCRETE WORKS INCLUDING KERBS.
5. COLOUR HARDENER (BURNT ORANGE OR RED) TO BE SPREAD AND TROWELLED AT A RATE OF 2KG/SQ.M AND AS PER MANUFACTURER'S SPECIFICATIONS.
6. MINIMUM 50mm COVER TOP AND BOTTOM TO ALL REINFORCEMENT. MESH TO BE SUPPORTED BY BAR CHAIRS AS PER AS3600.
7. PRAM CROSSING OPENING IN ISLAND TO ALIGN WITH PRAM CROSSINGS AND TACTILES EITHER SIDE OF ISLAND.
8. WORKS TO BE CONDUCTED IN ACCORDANCE WITH BCC STANDARD TMP AND TGS REQUIREMENTS AND CONDITIONS.



STANDARD TRAFFIC ISLAND DETAIL

APPROVED

Jani

PROJECT SERVICES
COORDINATOR

DRAWING No.

S420

DRAWN: D. WORSLEY

CHECKED: S.Q.

AMENDMENTS: AUG 2015

SCALE: N.T.S

DATE: MAY 2015

BY: D. WORSLEY