



NOTE:

- 1) WHERE COVER TO THE ROAD DRAINAGE IS IN THE RANGE 300mm TO 600mm. THE PROPERTY DRAIN MAY BE CONNECTED DIRECTLY INTO THE ROAD DRAINAGE. WHERE COVER EXCEEDS 600mm AN INSPECTION OPENING (27 2) SHOWN MUST BE USED BEHIND KERB.
- 3) WHERE UPVC HOUSE DRAINS ARE TO BE CONNECTED TO AN EXISTING COUNCIL DRAIN WHERE NO COLLAR EXISTS, A UPVC ADAPTOR WITH RUBBER RING MUST BE USED AT THE CONNECTION POINT. UPON CONNECTION THE COLLAR SHALL NOT PROTRUDE MORE THAN 10mm INTO EXISTING DRAIN.
- 4) ALL CONNECTIONS, BENDS AND INSPECTION POINTS TO BE MANUFACTURED BY THE PIPE SUPPLIER.
- 5) MINIMUM PIPE SIZE OF 100mm Ø SN10 UPVC-DWV TO BE USED IN FOOTPATH/VERGE.



PROPERTY INLET TO ROAD DRAINAGE

APPROVED

for
MANAGER
ENGINEERING SERVICES

DRAWING No.

S130

DRAWN: M BASILE

CHECKED: S.Q

AMENDMENTS: AUG 2018

SCALE: 1:20

DATE: AUG 2018

BY: M BASILE